

# ATENT COOPERATION TREATY

PCT

## NOTIFICATION OF THE RECORDING OF A CHANGE

(PCT Rule 92bis.1 and  
Administrative Instructions, Section 422)

From the INTERNATIONAL BUREAU

To:

ISHII, Kazuo  
Kitahama-Yamamoto Building  
3-6, Kitahama 2-chome, Chuo-ku  
Osaka-shi, Osaka 541-0041  
JAPON

Date of mailing (day/month/year)  
17 octobre 2001 (17.10.01)

Applicant's or agent's file reference  
P22089-PO

International application No.  
PCT/JP00/01359

### IMPORTANT NOTIFICATION

International filing date (day/month/year)  
06 mars 2000 (06.03.00)

#### 1. The following indications appeared on record concerning:

☒ the applicant ☒ the inventor ☐ the agent ☐ the common representative

#### Name and Address

KUMAKURA, Katsuhiko  
7-2-2, Hikaridai 5-chome  
Seikacho, Soraku-gun, Kyoto 619-0237  
Japan

State of Nationality  
JP

State of Residence  
JP

Telephone No.

Facsimile No.

Teleprinter No.

#### 2. The International Bureau hereby notifies the applicant that the following change has been recorded concerning:

☐ the person ☐ the name ☒ the address ☐ the nationality ☐ the residence

#### Name and Address

KUMAKURA, Katsuhiko  
7-3, Hikaridai 5-chome  
Seikacho, Soraku-gun, Kyoto 619-0237  
Japan

State of Nationality  
JP

State of Residence  
JP

Telephone No.

Facsimile No.

Teleprinter No.

#### 3. Further observations, if necessary:

#### 4. A copy of this notification has been sent to:

☒ the receiving Office ☐ the designated Offices concerned  
☐ the International Searching Authority ☒ the elected Offices concerned  
☐ the International Preliminary Examining Authority ☐ other:

The International Bureau of WIPO  
34, chemin des Colombettes  
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer

Shinji IGARASHI

Telephone No.: (41-22) 338.83.38

# PCT

## NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents  
United States Patent and Trademark  
Office  
Box PCT  
Washington, D.C.20231  
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing:

19 October 2000 (19.10.00)

International application No.:

PCT/JP00/01359

Applicant's or agent's file reference:

P22089-P0

International filing date:

06 March 2000 (06.03.00)

Priority date:

14 April 1999 (14.04.99)

Applicant:

KUMAKURA, Katsuhiko et al

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International preliminary Examining Authority on:

17 July 2000 (17.07.00)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was

☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO  
34, chemin des Colombettes  
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer:

J. Zahra

Telephone No.: (41-22) 338.83.38

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>P22089-P0</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/JP 00/01359</b>	International filing date (day/month/year) <b>06/03/2000</b>	(Earliest) Priority Date (day/month/year) <b>14/04/1999</b>
Applicant <b>MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. et al.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 04 sheets.



It is also accompanied by a copy of each prior art document cited in this report.

## 1. Basis of the report

- a. With regard to the language, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.



the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international search was carried out on the basis of the sequence listing:



contained in the international application in written form.



filed together with the international application in computer readable form.



furnished subsequently to this Authority in written form.



furnished subsequently to this Authority in computer readable form.



the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.



the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ Certain claims were found unsearchable (See Box I).

3. ☐ Unity of invention is lacking (see Box II).

## 4. With regard to the title,



the text is approved as submitted by the applicant.



the text has been established by this Authority to read as follows:

## 5. With regard to the abstract,



the text is approved as submitted by the applicant.



the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

## 6. The figure of the drawings to be published with the abstract is Figure No.



as suggested by the applicant.



because the applicant failed to suggest a figure.



because this figure better characterizes the invention.

1



None of the figures.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP 00/ 01359

## Box III TEXT OF THE ABSTRACT (Continuation of item 5 of the first sheet)

Deficiencies under Rule 8.1(d) are rectified as follows:

ln.1 :...package (1)...  
ln.2 :...articles (2)...  
ln.7 :...packages (2), an opening (3)...  
ln.9 :...lid (3)...  
ln.10 :...portion (4)...

## PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>P22089-P0</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/JP 00/ 01359</b>	International filing date (day/month/year) <b>06/03/2000</b>	(Earliest) Priority Date (day/month/year) <b>14/04/1999</b>
Applicant <b>MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. et al.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 04 sheets.



It is also accompanied by a copy of each prior art document cited in this report.

## 1. Basis of the report

- a. With regard to the language, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.



the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international search was carried out on the basis of the sequence listing:



contained in the international application in written form.



filed together with the international application in computer readable form.



furnished subsequently to this Authority in written form.



furnished subsequently to this Authority in computer readable form.



the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.



the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ Certain claims were found unsearchable (See Box I).

3. ☐ Unity of invention is lacking (see Box II).

## 4. With regard to the title,



the text is approved as submitted by the applicant.



the text has been established by this Authority to read as follows:

## 5. With regard to the abstract,



the text is approved as submitted by the applicant.



the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the drawing to be published with the abstract is Figure No.



as suggested by the applicant.



because the applicant failed to suggest a figure.



because this figure better characterizes the invention.

1



None of the figures.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP 00/01359

Box III TEXT OF THE ABSTRACT (Continuation of Item 5 of the first sheet)

Deficiencies under Rule 8.1(d) are rectified as follows:

ln.1 ....package (1)...  
ln.2 ....articles (2)...  
ln.7 ....packages (2), an opening (3)...  
ln.9 ....lid (3)...  
ln.10 ....portion (4)...

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 00/01359

**A. CLASSIFICATION OF SUBJECT MATTER**  
 IPC 7 B65D5/72

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
 IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 460 322 A (CARLSON TODD M ET AL) 24 October 1995 (1995-10-24)  abstract; figures 1,2,6-8 column 1, line 13 - line 47	1,2,4,5, 8,10,11, 14
Y	—	3,6,9, 12,15
Y	US 4 030 596 A (SNYDER ROBERT O ET AL) 21 June 1977 (1977-06-21) abstract; figures 4,5	3,9
Y	US 5 271 552 A (MCDONNELL JOHN) 21 December 1993 (1993-12-21) abstract; figure 1	6,12
	—	
	—/—	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 May 2000

Date of mailing of the international search report

25/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Mr Luca del Monte

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 00/01359

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 145 070 A (PALLET WILLIAM L ET AL) 8 September 1992 (1992-09-08) abstract; figure 1 column 3, line 28 - line 54	15
A	EP 0 770 563 A (FULLER ARTHUR GIBSON JR) 2 May 1997 (1997-05-02) abstract; figures 4,5,8,9	7,13



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 00/01359

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5460322	A	24-10-1995	NONE		
US 4030596	A	21-06-1977	NONE		
US 5271552	A	21-12-1993	CA	2084309 A	05-06-1994
US 5145070	A	08-09-1992	CA	2069226 A	05-03-1993
EP 0770563	A	02-05-1997	AU	5083096 A	01-05-1997
			US	5711423 A	27-01-1998

44/ 34 AMDT

## CLAIMS

1. (Amended) A dispensing package comprising:

a square-tubular case suitable for accommodating therein stacked unit packages, each package containing a plurality of stick-like articles aligned in parallel with the front wall of the case;

an opening for putting in and out the unit packages provided on an upper part of said square-tubular case;

a lid for closing said opening;

a bottom; and

an extracting outlet or a tear-off portion for forming an extracting outlet for extracting the unit package,

wherein the top surface of said bottom is inclined so that the front side of the bottom is lower than the rear side thereof and said extracting outlet or the tear-off portion is provided on a side wall of said case such that the unit package, which is to be placed on the top surface of the bottom, is taken out of the outlet from one end of the stick-like articles in the unit package.

2. (Amended) The dispensing package in accordance with claim 1, wherein said unit package contains a plurality of batteries aligned in parallel with the front wall of the case.

3. (Deleted)

4. (Amended) The dispensing package in accordance

AMENDED SHEET

11/2 2 cases?

09936757-091701

Unit package  
not positively  
recited.

ART 34 AMDT

with claim 1, wherein said case has a bottom surface with which the case can stand independently on a mounting board.

5. The dispensing package in accordance with claim 1, wherein a suspending piece for suspending the case is provided on a top end of the case.

6. (Amended) The dispensing package in accordance with claim 1, wherein at least the front wall of the case is transparent.

7. The dispensing package in accordance with claim 1, wherein a partition is placed on the unit package in the highest position in the case. *object to dug's partition not shown*

8. (Deleted)

9. (Deleted)

10. (Deleted)

11. (Deleted)

12. (Deleted)

13. (Deleted)

14. (Amended) The dispensing package in accordance with claim 1, wherein said package comprises a case assembled by a single sheet and a base having a top surface which is inclined so that the front side of the base is lower than the rear side thereof, said single sheet comprising:

a front wall, a rear wall and right and left side walls forming the square-tubular case;

flaps and a lid for closing the upper opening of the case; *additional lid?*

AMENDED SHEET

09936757-091701

*112 2nd  
is base separate?  
part of single sheet?*

a bottom wall constituting a bottom of the case; and  
a tear-off portion for forming the extracting  
outlet.

15. (Amended) The dispensing package in accordance  
with claim 1, wherein said package is assembled by a single  
sheet, said single sheet comprising:

a front wall, a rear wall and right and left side  
walls forming the square-tubular case;

flaps and a lid for closing the upper opening of the  
case; *another lid?*

a first base-forming portion including bottom wall  
pieces, upstanding pieces and top surface pieces that are  
respectively connected to the lower part of said right and  
left side walls; *2 base forming portions*

a bottom wall connected to the lower part of said  
front wall;

a second base-forming portion including an  
upstanding piece, a top surface piece and a down-standing  
piece that are respectively connected to the rear wall; and

a tear-off portion for forming the extracting  
outlet.

*add a 3y*

*as would*  
This application is a Section 371 of PCT/JP00/01359, published in English language on October 19, 2000 under WO 00/61444, the disclosure of which is incorporated herein by reference.--

**In the Claims:**

Please examine this application on the basis of the claims attached to the International Preliminary Examination Report.

Please add claim 16 as follows:

*a3*  
09936757-091701  
--16. A dispensing package comprising:  
a square-tubular case accommodating therein stacked unit packages, each package containing a plurality of cylindrical batteries aligned in parallel with the front wall of the case;  
an opening for putting in and out the unit packages provided on an upper part of said square-tubular case;  
a lid for closing said opening;  
a bottom; and  
an extracting outlet or a tear-off portion for forming an extracting outlet for extracting the unit package,  
wherein the top surface of said bottom is inclined so that the front side of the bottom is lower than the rear side thereof and said extracting outlet or the tear-off portion is provided on a side wall of said case such that <sup>which</sup> the unit package placed on the top surface of the bottom is taken out of the outlet from one end of the batteries in the unit package.--

*positively recites the batteries.*

*which outlet*  
**REMARKS**

Claims 1-2, 4-7 and 14-16 are pending in the application.

The purpose of this amendment is to insert the reference to the parent application of which this is a Section 371 national phase and to place the application headings in appropriate U.S. form along with adding an additional claim to this application. Such amendments are formal in nature and no new matter is added by any of the above amendments. A marked-up

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

9/9367574

REC'D 19 JUN 2001

WIPO PCT


Applicant's or agent's file reference P22089-P0		<b>FOR FURTHER ACTION</b> See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/JP00/01359	International filing date (day/month/year) 06/03/2000	Priority date (day/month/year) 14/04/1999	
International Patent Classification (IPC) or national classification and IPC B65D5/72			
Applicant MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD. et al.			

- This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
- This REPORT consists of a total of 4 sheets, including this cover sheet.
  - ☒ This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 7 sheets.

- This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☒ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 17/07/2000	Date of completion of this report 15.06.2001
Name and mailing address of the international preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465	Authorized officer Philippon, D Telephone No. +49 89 2399 2617



# INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/JP00/01359

## I. Basis of the report

1. With regard to the **elements** of the international application (*Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)*):

### Description, pages:

2,5-20 as originally filed

1,1a,3,4 as received on 11/04/2001 with letter of 09/04/2001

### Claims, No.:

1,2,4-7,14,15 as received on 11/04/2001 with letter of 09/04/2001

### Drawings, sheets:

1/8-8/8 as originally filed

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language: , which is:

- ☐ the language of a translation furnished for the purposes of the international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of a translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. The amendments have resulted in the cancellation of:

**INTERNATIONAL PRELIMINARY  
EXAMINATION REPORT**

International application No. PCT/JP00/01359

- ☐ the description,      pages:  
☐ the claims,      Nos.:  
☐ the drawings,      sheets:

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

*(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)*

6. Additional observations, if necessary:

**V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**

1. Statement

Novelty (N)	Yes:	Claims	1,2,4-7, 14,15
	No:	Claims	
Inventive step (IS)	Yes:	Claims	1,2,4-7,14,15
	No:	Claims	
Industrial applicability (IA)	Yes:	Claims	1,2,4-7,14,15
	No:	Claims	

2. Citations and explanations  
**see separate sheet**

**VII. Certain defects in the international application**

The following defects in the form or contents of the international application have been noted:  
**see separate sheet**



Item V

The dispensing package according to claim 1 differs from the nearest available prior art as represented by the disclosure of D1 = US-A-5 460 322 in that the top surface of the bottom is inclined so that the front side of the bottom is lower than the rear side thereof, whereby the extracting outlet or the tear-off portion for forming said outlet is provided on a side wall of the case and is consequently also inclined. Such a modification of the package according to D1 is not suggested by the prior art. The subject-matter of claim 1 thus involves an inventive step (Article 33 PCT).

Claims 2,4-7, 14,15 are dependent on claim 1 and as such also meet the requirements of the PCT with respect to novelty and inventive step.

Item VII

Independent claim 1 is not in the two-part form in accordance with Rule 6.3(b) PCT, which in the present case would be appropriate, with those features known in combination from the prior art (document D1) being placed in the preamble (Rule 6.3(b)(i) PCT) and with the remaining features being included in the characterising part (Rule 6.3(b)(ii) PCT).

The features of the claims are not provided with reference signs placed in parentheses (Rule 6.2(b) PCT).

The claims are not numbered consecutively (Rule 6.1 (b) ).

## DESCRIPTION

## DISPENSING PACKAGE

## Technical Field

The present invention relates to a dispensing package for accommodating and displaying stick-like small articles, especially small-sized cylindrical batteries such as AA size batteries for sales purpose or the like.

## Background Art

Various kinds of packages for accommodating batteries and other daily necessities are commercially available. U.S. Patent No. 5,460,322 discloses a dispensing container comprising: a case suitable for accommodating therein a plurality of products; an opening provided on an upper part of the case; a lid for closing the opening; and a tear-out flap for forming an extracting outlet provided on the sidewall adjacent its bottom end. In the field of batteries, widely used are so-called shrink-packages or blister-packages in which two or four batteries are wrapped by means of heat-shrinkable resin tubes. When such packages for accommodating articles are displayed, being aligned on a showcase at a storefront or suspended, customers can visually confirm with ease types, grades or brand names of contents, and the packages for accommodating articles are also conveniently portable.

1/1

However, with improvements in high-functional apparatuses utilizing batteries in these years, there exists a tendency that the number of utilized batteries are increasing or that the frequency of exchanging batteries is increasing, therefore battery packages that are capable of accommodating a large number of batteries are increasingly in demand. Such

Further object of the present invention is to provide a dispensing package with which a specified number of articles can be taken out in a smooth manner.

#### Disclosure of Invention

The present invention provides a dispensing package comprising:

- a square-tubular case suitable for accommodating therein stacked unit packages, each package containing a plurality of stick-like articles aligned in parallel with the front wall of the case;

- an opening for putting in and out the unit packages provided on an upper part of said square-tubular case;

- a lid for closing said opening;

- a bottom; and

- an extracting outlet or a tear-off portion for forming an extracting outlet for extracting the unit package,

wherein the top surface of said bottom is inclined so that the front side of the bottom is lower than the rear side thereof and said extracting outlet or the tear-off portion is provided on a side wall of said case such that the unit package, which is to be placed on the top surface of the bottom, is taken out of the outlet from one end of the stick-like articles in the unit package.

The present invention further provides a battery dispensing package having a structure as described above.

While the novel features of the invention are set forth particularly in the appended claims, the invention, both as to organization and content, will be better understood and appreciated, along with other objects and features thereof, from the following detailed description taken in conjunction with the drawings.

#### Brief Description of Drawings

Fig. 1 is a perspective view of a dispensing package according to one embodiment of the present invention.

Fig. 2 is a perspective view of a battery package employed in the same embodiment.

Fig. 3 is a perspective view of a dispensing package according to another embodiment of the present invention.

Fig. 4 is an exploded view of a sheet constituting a dispensing package according to the same embodiment.

Fig. 5 is a perspective view showing assembling processes of the same dispensing package.

Fig. 6 is a perspective view showing a condition in which assembly has further progressed.

## CLAIMS

1. (Amended) A dispensing package comprising:  
a square-tubular case suitable for accommodating therein stacked unit packages, each package containing a plurality of stick-like articles aligned in parallel with the front wall of the case;

an opening for putting in and out the unit packages provided on an upper part of said square-tubular case;

a lid for closing said opening;

a bottom; and

an extracting outlet or a tear-off portion for forming an extracting outlet for extracting the unit package,

wherein the top surface of said bottom is inclined so that the front side of the bottom is lower than the rear side thereof and said extracting outlet or the tear-off portion is provided on a side wall of said case such that the unit package, which is to be placed on the top surface of the bottom, is taken out of the outlet from one end of the stick-like articles in the unit package.

2. (Amended) The dispensing package in accordance with claim 1, wherein said unit package contains a plurality of batteries aligned in parallel with the front wall of the case.

3. (Deleted)

4. (Amended) The dispensing package in accordance

with claim 1, wherein said case has a bottom surface with which the case can stand independently on a mounting board.

5. The dispensing package in accordance with claim 1, wherein a suspending piece for suspending the case is provided on a top end of the case.

6. (Amended) The dispensing package in accordance with claim 1, wherein at least the front wall of the case is transparent.

7. The dispensing package in accordance with claim 1, wherein a partition is placed on the unit package in the highest position in the case.

8. (Deleted)

9. (Deleted)

10. (Deleted)

11. (Deleted)

12. (Deleted)

13. (Deleted)

14. (Amended) The dispensing package in accordance with claim 1, wherein said package comprises a case assembled by a single sheet and a base having a top surface which is inclined so that the front side of the base is lower than the rear side thereof, said single sheet comprising:

a front wall, a rear wall and right and left side walls forming the square-tubular case;

flaps and a lid for closing the upper opening of the case;

a bottom wall constituting a bottom of the case; and  
a tear-off portion for forming the extracting  
outlet.

15. (Amended) The dispensing package in accordance  
with claim 1, wherein said package is assembled by a single  
sheet, said single sheet comprising:

a front wall, a rear wall and right and left side  
walls forming the square-tubular case;

flaps and a lid for closing the upper opening of the  
case;

a first base-forming portion including bottom wall  
pieces, upstanding pieces and top surface pieces that are  
respectively connected to the lower part of said right and  
left side walls;

a bottom wall connected to the lower part of said  
front wall;

a second base-forming portion including an  
upstanding piece, a top surface piece and a down-standing  
piece that are respectively connected to the rear wall; and

a tear-off portion for forming the extracting  
outlet.





## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification<sup>7</sup>:

B65D 5/72

A1

(11) International Publication Number:

WO 00/61444

(43) International Publication Date:

19 October 2000 (19.10.00)

(21) International Application Number: PCT/JP00/01359

(22) International Filing Date: 6 March 2000 (06.03.00)

(30) Priority Data:

11/106679

14 April 1999 (14.04.99)

JP

(71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza-Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KUMAKURA, Katsuhiko [JP/JP]; 7-2-2, Hikaridai 5-chome, Seikacho, Soraku-gun, Kyoto 619-0237 (JP). ONO, Tadashi [JP/JP]; 8-3, Kuzuha-Noda 1-chome, Hirakata-shi, Osaka 573-1103 (JP).

(74) Agent: ISHII, Kazuo; Kitahama-Yamamoto Building, 3-6, Kitahama 2-chome, Chuo-ku, Osaka-shi, Osaka 541-0041 (JP).

(81) Designated States: CN, ID, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report.

(54) Title: DISPENSING PACKAGE

## (57) Abstract

A dispensing package (1) that is capable of accommodating a relatively large number of stick-like articles (2), of separating old and new articles and of storing remaining articles is disclosed. This dispensing package comprises a case for accommodating therein unit packages containing a plurality of stick-like articles like batteries aligned in parallel by stacking a plurality of unit packages (2), an opening (3) for putting in and taking out the unit packages provided on an upper part of the case, a lid (3) for closing the opening, and a tear-off portion (4) for forming the extracting outlet that is provided on a side wall corresponding to the unit package in the lowest position. The extracting outlet is formed on a side wall of the case facing to one end of the stick-like articles in the unit package. A large number of articles can be effectively displayed and a specified number of articles can be taken out smoothly.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## DESCRIPTION

## DISPENSING PACKAGE

## Technical Field

The present invention relates to a dispensing package for accommodating and displaying stick-like small articles, especially small-sized cylindrical batteries such as AA size batteries for sales purpose or the like.

## Background Art

Various kinds of packages for accommodating batteries and other daily necessities are commercially available. In the field of batteries, widely used are so-called shrink-packages or blister-packages in which two or four batteries are wrapped by means of heat-shrinkable resin tubes. When such packages for accommodating articles are displayed, being aligned on a showcase at a storefront or suspended, customers can visually confirm with ease types, grades or brand names of contents, and the packages for accommodating articles are also conveniently portable.

However, with improvements in high-functional apparatuses utilizing batteries in these years, there exists a tendency that the number of utilized batteries are increasing or that the frequency of exchanging batteries is increasing, therefore battery packages that are capable of accommodating a large number of batteries are increasingly in demand. Such

demands cannot be sufficiently satisfied with conventional shrink-packages or blister-packages.

In view of this point, it has been proposed to increase the number of accommodated batteries in shrink-packages or blister-packages and also a transparent plastic case for accommodating a large number of batteries by stacking has been proposed.

However, if merely the number of batteries is increased, the batteries scatter when the package is opened so that keeping of the batteries becomes troublesome for users. In the case of blister-packages, not only the number of batteries that can be displayed is restricted but also unnecessary portions such as "hems" of mounting board are increased to result in higher costs.

An object of the present invention is to provide a dispensing package that can solve the above inconveniences of conventional packages and that can accommodate a large number of small articles, especially batteries, and also convenient for users.

Another object of the present invention is to provide a dispensing package with which a large number of articles can be displayed in an effective manner.

Still another object of the present invention is to provide a dispensing package with which a specified number of articles can be taken out from the dispensing package in a systematic manner during storage.

Further object of the present invention is to provide a dispensing package with which a specified number of articles can be taken out in a smooth manner.

#### Disclosure of Invention

The present invention provides a dispensing package comprising a case for accommodating therein unit packages by stacking a plurality of unit packages containing a plurality of stick-like articles aligned in parallel, an opening for putting in and out the unit packages provided on an upper part of the case, a lid for closing the opening, and an extracting outlet for extracting the unit packages or a tear-off portion for forming the extracting outlet that is provided on a side wall corresponding to the unit package in the lowest position.

Here, it is preferable that the case is a square-tubular case and that the extracting outlet or the tear-off portion for forming the extracting outlet is provided on a side wall of the case facing to one end of stick-like articles in the unit package.

The present invention further provides a battery dispensing package comprising a square-tubular case for accommodating therein unit packages by stacking a plurality of unit packages containing a plurality of batteries aligned in parallel, an opening for putting in and taking out the unit packages, a lid for closing the opening, and a tear-off portion for forming an extracting outlet for extracting the

unit package that is provided on a side wall facing to one end of the batteries in the unit package in the lowest position in the case.

It is preferable that the unit packages are accommodated in such a way that they are inclined so that the front side of the case is lower and the rear side is higher.

While the novel features of the invention are set forth particularly in the appended claims, the invention, both as to organization and content, will be better understood and appreciated, along with other objects and features thereof, from the following detailed description taken in conjunction with the drawings.

#### Brief Description of Drawings

Fig. 1 is a perspective view of a dispensing package according to one embodiment of the present invention.

Fig. 2 is a perspective view of a battery package employed in the same embodiment.

Fig. 3 is a perspective view of a dispensing package according to another embodiment of the present invention.

Fig. 4 is an exploded view of a sheet constituting a dispensing package according to the same embodiment.

Fig. 5 is a perspective view showing assembling processes of the same dispensing package.

Fig. 6 is a perspective view showing a condition in which assembly has further progressed.

Fig. 7 is an exploded view of a modified example of the same dispensing package.

Fig. 8 is a perspective view of a dispensing package according to still another embodiment of the present invention.

Fig. 9 is a perspective view of a base that is to be combined with the same package.

Fig. 10 is a perspective view showing a bottom of the same package.

Fig. 11 is an exploded view showing a sheet comprising the same package.

#### Best Mode for Carrying Out the Invention

As explained above, the dispensing package according to the present invention accommodates unit packages containing a plurality of articles aligned in parallel by stacking a plurality of the unit packages, and a tear-off portion for forming an extracting outlet for extracting the unit package is provided on a side wall corresponding to the unit package in the lowest position. A customer who has purchased such a dispensing package can form an extracting outlet for the unit package by tearing off the tear-off portion. Thus, the unit package can be extracted from the extracting outlet when articles are required for use. The remaining unit packages can be stored in the dispensing package. In this manner, the dispensing package according to the present invention is not only capable of accommodating relatively a large number of

articles but also of separating old and new articles as well as of storing remaining articles.

In a preferred mode for carrying out the present invention, articles to be accommodated are cylindrical like batteries, and the extracting outlet is formed on a side wall of the case facing one end of articles in the unit package in the lowest position. When extracting the unit package, the unit package in the lowest position, which is to be taken out, is applied with weight of unit packages that are stacked thereon. However, in the above-described arrangement, when extracting the unit package, articles in the package are pulled out by being slid in an axial direction to articles in overlying packages. Thus, in spite of the load of the unit packages that are stacked thereon is applied, the lowest unit package can be taken out smoothly.

In another preferred mode for carrying out the present invention, unit packages are accumulated so that the side facing the front wall of the case is lower and the side facing the rear wall is higher. According to this arrangement, the depth of the dispensing package can be reduced so that display densities can be improved at limited spaces. Further, in addition to the provision of the extracting outlet on the side wall of the case, a part of the load of the overlying packages exerts on the front wall of the case when the unit package is extracted, so the unit package can be extracted even easier. Similarly, by arranging the lid of the case to



be inclined, indications related to types, grades or brands of contents displayed on the lid are visible from the front, therefore displaying effects can also be improved.

The dispensing package of the present invention is preferably provided with a bottom wall with which the case can stand independently on a mounting board or with a suspending piece for suspending the case on a top end of the case. By arranging the package to be of desktop-type and/or suspending-type, articles can be stored in a visible manner to be ready for use.

In another preferred mode for carrying out the present invention, at least the front wall of the case is transparent. With this arrangement, the unit packages in the case can be confirmed from outside. Especially when the unit packages are shrink-packages utilizing transparent resin, the articles themselves can be visually confirmed from outside. With this arrangement, types, grades or brands of articles that are marked on the articles can be easily confirmed in a visual manner so that displaying effects can be improved. Further, by applying designs on the lid or by making an arrangement with which contents can be visually confirmed, displaying effects can be further improved.

In still another mode for carrying out the present invention, a partition is placed on the unit package in the highest position in the case. By putting, for instance, used batteries on the partition, it is also convenient to collect

waste materials.

In a preferred mode for carrying out the present invention, a dispensing package is assembled by a single sheet and the single sheet comprises:

a front wall, a rear wall and right and left side walls forming a square-tubular case for accommodating unit packages by stacking a plurality of unit packages;

flaps and a lid for closing an upper opening of the case;

a bottom wall constituting a bottom of the case; and

a tear-off portion for forming an extracting outlet for extracting a unit package in the lowest position in the case that is provided either on the left side wall or on the right side wall.

If necessary, a suspending portion may be formed at a top end of the case, for instance, on the rear wall. A base for placing the unit packages thereon can be inserted inside the case.

In still another preferred mode for carrying out the present invention, a dispensing package is assembled by a single sheet and the single sheet comprises:

a front wall, a rear wall and right and left side walls forming a square-tubular case for accommodating unit packages by stacking a plurality of unit packages;

flaps and a lid for closing an upper opening of the case;

a first base-forming portion including bottom wall pieces, upstanding pieces and top surface pieces that are respectively connected to the lower part of the right and left side walls;

a bottom wall connected to the lower part of the front wall;

a second base-forming portion including an upstanding piece, a top surface piece and a down-standing piece that are respectively connected to the rear wall; and

a tear-off portion for forming an extracting outlet for extracting the unit package in the lowest position in the case that is provided either on the left side wall or on the right side wall.

According to this arrangement, a base onto which the unit packages are placed can be incorporated into the case. Since this base is provided with legs constituted by the upstanding piece and the down-standing piece, the base is strong enough to stand the load of stacked unit packages. If necessary, a suspending portion may be formed at a top end of the case, for instance, on the rear wall.

Next, concrete embodiments will be explained.

#### Embodiment 1

Fig. 1 shows an example of a dispensing package, and Fig. 2 shows, as a unit package for articles, a unit package 6 of a shrink-package made of a transparent resin tube 8 in

which four cylindrical AA size batteries 7, for instance, are aligned in parallel with each other and packed by heat-shrinkage of the resin tube.

The dispensing package 1 comprises a square-tubular case 2 for stacking a plurality of unit packages 6 and a lid 3 which closes an upper opening of the case. A base 4 is inserted into a bottom portion of the case 2. The base 4 is made of plastic and formed into a square-tubular shape having an open bottom surface and a top surface being inclined so that a front side is lower and a rear side is higher. The unit packages 6 are stacked on the base 4 in the case 2 in such a way that they are inclined so that their front side is lower. An extracting outlet 5 for extracting the unit package in the lowest position is formed on the right side wall of the case 2. The extracting outlet 5 is formed by tearing off a tear-off portion that have been preliminarily marked off by means of perforations in the portion constituting the right side wall of the case. The dispensing package has a bottom wall with which it can stand independently on a table. If necessary, a piece for suspending the case having a suspending hole may be provided on a part of the case, for instance, on a rear wall.

In this example, the dispensing package 1 is made of transparent plastic sheet such as polyethylene terephthalate. The unit packages 6 are stacked so that the ends of the batteries face to the side walls of the dispensing package and

so that the trunk portion of the batteries are positioned to the front of the dispensing package, therefore the types, grades or brands that are marked on the batteries can be visually confirmed from the front of the dispensing package. The extracting outlet 5 for extracting each unit package is provided on the side wall facing one end of the batteries 7 in the unit package 6, so the unit package is pulled out in an axial direction of the batteries contained therein when extracting the unit package. At this time, the trunk portion of the batteries of the unit package to be extracted are made to slide in an axial direction to the trunk portion of the batteries of an overlying unit package so that the unit package can be easily extracted in spite of the load of the overlying unit packages. If the unit package is to be extracted in a vertical direction to the axe of the batteries, it cannot be extracted easily because concaves and convexes extending in a vertical direction to the extracting direction are formed on the top surface of the unit package.

While the extracting outlet is formed on the side wall of the case, it may also be formed on the front wall or the rear wall of the case. The material for the case is not limited to plastic, and it is also possible to use paper or the like.

## Embodiment 2

In this embodiment, the base portion according to

Embodiment 1 is also assembled by a sheet constituting a dispensing package.

Fig. 3 illustrates an assembled dispensing package and Fig. 4 is an exploded view of a sheet constituting the package.

A sheet 10 constituting the dispensing package is made of a sheet of plastic or paper punch-processed by using a specified mold, and folding marks and perforations that are to be described later are formed on the sheet at the same time.

Numerical 11 denotes a front wall and a left side wall 12 is connected via a folding mark 11a to the left of the front wall 11 and a right side wall 13 via a folding mark 11b on the right of the front wall 11, respectively. A rear wall 14 is connected to further right to the right side wall 13 via a folding mark 13a, and a margin for paste 15 to the left side wall 12 via a folding mark 12a.

An upper wall 21 and a bottom wall 31 are connected to above and below, respectively, of the front wall 11, via folding marks 11c and 11d, respectively. Further, an inserting piece 41 is connected to the upper wall 21 via a folding mark 21c and an inserting piece 51 is connected to the bottom wall 31 via a folding mark 31d. Cuts 21e are provided at both ends of the folding mark 21c and cuts 31e are provided at both ends and the center of the folding mark 31d.

A flap 22 is provided on an upper portion of the left side wall 12 via a folding mark 12c, and on a lower

portion of the left side wall 12, there are sequentially provided a folding mark 12d, bottom wall piece 32, folding mark 32d, upstanding piece 52, folding mark 52d and a top surface piece 62.

On an upper portion of the right side wall 13, a flap 23 is provided via a folding mark 13c, and on a lower portion of the right side wall 13, there are sequentially provided a folding mark 13d, bottom wall piece 33, folding mark 33d, upstanding piece 53, folding mark 53d and a top surface piece 63.

On a lower portion of the rear wall 14, there are sequentially formed a folding mark 14d, upstanding piece 54, folding mark 54d, a top surface piece 34, a folding mark 34d, and an down-standing piece 55.

A tear-off portion 16 is marked off by means of perforations 13e and 13f on the right side wall 13 and apertures 17 and 18 are respectively provided on the front wall 11 and the rear wall 14 adjacent to the right and the left of the tear-off portion. An aperture 19 is formed on the left side wall 12.

A method for assembling the dispensing package by using the sheet 10 will be explained now.

Fig. 5 and Fig. 6 are perspective views of assembling processes when seen from the side of the front wall 11.

First, the left side wall 12, the margin for paste

15, the right side wall 13 and the rear wall 14 are bent at right angles to respective adjoining pieces so that the folding marks 11a, 11b, 12a and 13a face outward. The margin for paste 15 is adhered to inner surface of the rear side wall 14 at a proper step of assembly.

Next, the bottom wall piece 32, upstanding piece 52 and the top surface piece 62 are bent at right angles to their adjoining pieces so that the folding marks 12d, 32d and 52d face outward. Similarly, the bottom wall piece 33, upstanding piece 53 and the top surface piece 63 are bent at right angles to their adjoining pieces at the folding marks 13d, 33d and 53d.

Then, the bottom wall 31 and the inserting piece 51 are bent at right angles at folding marks 11d and 31d.

Furthermore, the upstanding piece 54 is bent at folding mark 14d and is overlapped to an inner surface of the rear wall 14 and the top surface piece 34 and the down-standing piece 55 are bent to make right angles to adjoining pieces so that the folding marks 54d and 34d face inward.

Then, by placing the bottom wall piece 32 on an top surface of the bottom wall 31, the top surface piece 62 forms a base portion 31L having a lower front side between the rear wall 14 and the upstanding piece 54 that has been overlapped onto the inner surface of the front wall 11 and on the left half of the bottom wall 31 by using the upstanding piece 52 as a leg. Similarly, the top surface piece 63 forms a base



portion 31R having a lower front side between the rear wall 14 and the upstanding piece 54 and on the right half of the bottom wall 31 by using the upstanding piece 53 as a leg.

Upper surfaces of the base portions 31L and 31R are covered by the top surface piece 34 and the down-standing piece 55 connected to the top surface piece 34 is inserted between the front wall 11 and the base portions 31L and 31R to come in contact with the bottom wall 31. The inserting piece 51 connected to the bottom wall 31 is inserted between the rear wall 14 and the base portions 31L and 31R.

In this manner, a base is formed using the bottom wall piece 32, upstanding piece 52, and the top surface piece 62 that are connected to the left side wall 12 and bottom wall piece 33, upstanding piece 53, and the top surface piece 63 that are connected to the right side wall 13, the upstanding piece 54, top surface piece 34, and the down-standing piece 55 that are connected to the rear wall 14 cover the base, and the upstanding piece 54 and down-standing piece 55 serve as legs, so that it is possible to form a base that is strong enough to stack unit packages thereon even if it is made of a thin sheet.

Through these steps, it is possible to assemble a dispensing package having an upper opening. This opening is closed by bending the flaps 22 and 23 at the folding marks 12c and 13c at right angles to the left side wall 12 and the right side wall 13, respectively, bending the upper wall 21 at the folding mark 11c and also bending the inserting piece 41 at

the folding mark 21c to make it inserted between the rear wall 14 and the flaps 22 and 23.

In this manner, the dispensing package including a support base for stacking the unit packages thereon composed of the base portions 31L and 31R and the top surface piece 34 covering the base portions is completed. It is possible to insert and stack five unit packages 6 through its upper opening, close the lid and affix a seal for display at a storefront.

Fig. 7 shows a modified example of the above-described sheet. In this example, a tongue-shaped piece 16a is formed by providing a folding mark 13h and a cut mark 13g on a part of the tear-off portion 16, while a tongue-shaped piece 34a that has been cut and raised at a cut mark 34g is formed on the top surface piece 34 that forms the base portion. Then, when assembling the dispensing package, the tongue-shaped piece 16a is bent inward, the top surface piece 34 is overlapped thereon, and a tip end of the tongue-shaped piece 16a is inserted to be pinched between the top surface piece 34 and the tongue-shaped piece 34a by slightly pressing down the tongue piece 34a. In this manner, the base portion can be strengthened.

### Embodiment 3

The present embodiment illustrates an example in which the base portion for stacking the unit packages thereon

is formed separately from the sheet for assembling the package. Fig. 8 is a perspective view of an assembled package, Fig. 9 is a perspective view showing a base to be inserted into the bottom portion of the package, and Fig. 10 is a perspective view showing a bottom wall of the package.

First, a sheet constituting the package will be explained with reference to the exploded view as shown in Fig. 11.

Numeral 111 denotes a front wall. A left side wall 112 is provided on the left side of the front wall 111 via a folding mark 111a, and to the left of the left side wall 112, a margin for paste 115 is provided via a folding mark 112a. A right side wall 113 is provided on the right side of the front wall 111 via a folding mark 111b, and to the right of the right side wall 113, a rear wall 114 is provided via a folding mark 113a.

On an upper portion of the front wall 111, there is provided a top wall 121 via a folding mark 111c and on an upper portion of the top wall 121, an inserting piece 141 is provided via a folding mark 121c. On a lower portion of the front wall 111, there is provided a bottom wall piece 131 via a folding mark 111d. At both ends of the folding mark 121c, there are provided cuts 121e.

A flap 122 is provided on an upper portion of the left side wall 112 via a folding mark 112c, and on a lower portion of the left side wall 112, a bottom wall piece 132 is

provided via a folding mark 112d.

Similarly, a flap 123 is provided on an upper portion of the right side wall 113 via a folding mark 113c and on an lower portion of the right side wall 113, a bottom wall piece 133 is provided via a folding mark 113d.

A lapel piece 124 is provided at an upper portion of the rear wall 114 via a folding mark 114c and the lapel piece 124 and a corresponding portion of the rear wall 114 are provided with suspending holes 125B and 125A by punching. At a lower portion of the rear wall 114, a bottom wall piece 134 is provided via a folding mark 114d.

A tear-off portion 116 is marked off by means of perforations 113e and 113f on the right side wall 113 and apertures 117 and 118 are respectively provided on the front wall 111 and the rear wall 114 adjacent to the right and the left of the tear-off portion. An aperture 119 is formed on the left side wall 112.

In order to assemble the dispensing package by using the sheet 100, the sheet is bent at right angles at the folding marks 111a, 111b, 112a and 113a so that the folding marks face outward, and the margin for paste 115 is adhered to the rear wall 114.

Thereafter, the bottom wall pieces 131, 132, 133 and 134 are bent inward at right angles at the folding marks 111d, 112d, 113d and 114d. At this time, the bottom wall piece 134 is placed onto the bottom wall pieces 132 and 133, and a tip

end of an extruding piece 131A of the bottom wall piece 131 is inserted inward of the bottom wall piece 134 from a bottom portion of a notched portion 134A of the bottom wall piece 134. With this arrangement, the tip end of the extruding piece 131A is pinched between the bottom wall piece 134 and the bottom wall pieces 132 and 133, so that a tapered portion 131B connected to the extruding piece 131A presses against inward end portions of both tip end portions 134B of the bottom wall piece 134. In this way, a dispensing package having a closed bottom and an upper opening is produced.

Then, the base 131 is inserted into the dispensing package. The base 131 is formed so that the top surface and the four side walls are molded, with the top surface inclined in such a way that the front side is lower and the rear side is higher.

Next, the flaps 122 and 123 are bent inward at the folding marks 112c and 113c, then the upper wall 121 is bent inward at the folding mark 111c and the inserting piece 141 is bent at the folding mark 121c, and subsequently insert the inserting piece 141 is inserted between the rear wall 114 and the flaps 122 and 123, thereby to close the opening of the dispensing package.

The dispensing package as illustrated herein is for stacking unit packages of, for instance, two AAA size batteries aligned with each other.

### Industrial Applicability

As explained above, the present invention provides a dispensing package that can, not only store a relatively large number of articles but can also separate used and new articles and store articles in stock, and further can exhibit great displaying effects.

## CLAIMS

1. A dispensing package comprising:

a case for accommodating therein unit packages containing a plurality of stick-like articles aligned in parallel by stacking a plurality of unit packages;

an opening for putting in and taking out said unit packages provided on an upper part of said case;

a lid for closing said opening; and

an extracting outlet for extracting the unit package or a tear-off portion for forming the extracting outlet that is provided on a side wall corresponding to the unit package placed in the lowest position in said case.

2. The dispensing package in accordance with claim 1, wherein said case is a square-tubular case and said extracting outlet or the tear-off portion for forming the extracting outlet is provided on a side wall of said case facing one end of stick-like articles in said unit package.

3. The dispensing package in accordance with claim 2, wherein said unit packages are accommodated in such a way that they are inclined so that the side facing the front wall of the case is lower and the side facing the rear wall is higher.

4. The dispensing package in accordance with claim 2, wherein said case has a bottom surface with which the case can stand independently on a mounting board.

5. The dispensing package in accordance with claim

1, wherein a suspending piece for suspending the case is provided on a top end of the case.

6. The dispensing package in accordance with claim 1, wherein at least a front wall of the case is transparent.

7. The dispensing package in accordance with claim 1, wherein a partition is placed on the unit package in the highest position in the case.

8. A dispensing package comprising:

a square-tubular case for accommodating therein unit packages containing a plurality of batteries aligned in parallel by stacking a plurality of unit packages;

an opening for putting in and out the unit packages provided on an upper part of said square-tubular case;

a lid for closing said opening; and

an extracting outlet for extracting the unit package or a tear-off portion for forming an extracting outlet for extracting the unit package that is provided on a side wall facing one end of the batteries in the unit package placed in the lowest position in said square-tubular case.

9. The dispensing package in accordance with claim 8, wherein said unit packages are accommodated in such a way that they are inclined so that the side facing the front wall of the case is lower and the side facing the rear wall is higher.

10. The dispensing package in accordance with claim 8, wherein said square-tubular case has a bottom wall with



which the case can stand independently on a mounting board.

11. The dispensing package in accordance with claim 8, wherein a suspending piece for suspending the case is provided on a top end of the case.

12. The dispensing package in accordance with claim 8, wherein at least a front wall of the case is transparent.

13. The dispensing package in accordance with claim 8, wherein a partition is placed on the unit package in the highest position in the case.

14. A dispensing package that is assembled by a single sheet, said single sheet comprising:

a front wall, a rear wall and right and left side walls forming a square-tubular case for accommodating unit packages by stacking a plurality of unit packages;

flaps and a lid for closing an upper opening of the case;

a bottom wall constituting a bottom of the case; and

a tear-off portion for forming an extracting outlet for extracting a unit package in the lowest position in the case that is provided either on the left side wall or on the right side wall.

15. A dispensing package that is assembled by a single sheet, said single sheet comprising:

a front wall, a rear wall and right and left side walls forming a square-tubular case for accommodating unit packages by stacking a plurality of unit packages;

flaps and a lid for closing an upper opening of the case;

a first base-forming portion including bottom wall pieces, upstanding pieces and top surface pieces that are respectively connected to the lower part of said right and left side walls;


a bottom wall connected to the lower part of said front wall;

a second base-forming portion including an upstanding piece, a top surface piece and a down-standing piece that are respectively connected to the rear wall; and

a tear-off portion for forming an extracting outlet for extracting the unit package in the lowest position in the case that is provided either on the left side wall or on the right side wall.

1/8

FIG. 1



2/8

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 9




FIG. 10





FIG. 11



# INTERNATIONAL SEARCH REPORT

Inter.      nal Application No

PCT/JP 00/01359

**A. CLASSIFICATION F SUBJECT MATTER**  
IPC 7      B65D5/72

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7      B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 460 322 A (CARLSON TODD M ET AL) 24 October 1995 (1995-10-24)  abstract; figures 1,2,6-8 column 1, line 13 - line 47	1,2,4,5, 8,10,11, 14
Y		3,6,9, 12,15
Y	US 4 030 596 A (SNYDER ROBERT O ET AL) 21 June 1977 (1977-06-21) abstract; figures 4,5	3,9
Y	US 5 271 552 A (MCDONNELL JOHN) 21 December 1993 (1993-12-21) abstract; figure 1	6,12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 May 2000

Date of mailing of the international search report

25/05/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Mr Luca del Monte

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 00/01359

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 145 070 A (PALLET WILLIAM L ET AL) 8 September 1992 (1992-09-08) abstract; figure 1 column 3, line 28 - line 54	15
A	EP 0 770 563 A (FULLER ARTHUR GIBSON JR) 2 May 1997 (1997-05-02) abstract; figures 4,5,8,9	7,13

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/JP 00/01359

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5460322	A	24-10-1995	NONE	
US 4030596	A	21-06-1977	NONE	
US 5271552	A	21-12-1993	CA 2084309 A	05-06-1994
US 5145070	A	08-09-1992	CA 2069226 A	05-03-1993
EP 0770563	A	02-05-1997	AU 5083096 A	01-05-1997
			US 5711423 A	27-01-1998